

ALGACID ACTIVE MOULD REMOVER

**PORCELAIN TILES, NATURAL STONE,
CERAMIC, CLINKER, CONCRETE AND
GROUTING, TERRACOTTA, QUARRY TILES**



WHAT IT'S FOR

- Rapidly removes mould and sanitises stone, plaster, concrete, terracotta, grouting, ceramic, glass and marmorino plaster surfaces.

ADVANTAGES

- Easy-to-use, ergonomic container with spray applicator.
- Ideal viscosity: can be easily applied to walls.
- Acts rapidly and effectively within a few minutes.
- Effectively removes mould from grouting.

HOW TO USE IT

Ready to use: no dilution required.

Application: Spray **ALGACID** directly onto the surface to be cleaned, from a distance of about 15-20 cm, while keeping the bottle upright. Leave to act for approximately 15 minutes. Soak up any excess product with a damp cloth to prevent dripping. Repeat if necessary, then wipe the surface clean with a damp sponge.

Caution:

*do not spray on wood, plants, fabrics and metals. Should this occur, wash immediately with water. Do not use on new polished stone.
Caution: before using on coloured plaster, first try on a small section to avoid possible colour alterations.
Use biocides safely. Always read the label and product information before use.*



COVERAGE

With one litre:

**10-20 m² depending on surface
absorption**

The coverage is purely indicative

Packaging

500 ml bottles with spray nozzle in boxes of 6.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Do not use in conjunction with acids. It may produce hazardous gas (chlorine).
- Ventilate the room during and after application.
- Do not remove dry mould in order to prevent dispersion of the spores.

TEMPERATURES

Storage temperature: from 5° to 30° C.
The product should be applied to materials with temperature between 5° and 30° C.