

## WET-EFFECT TONING PROTECTIVE TREATMENT

**UNPOLISHED NATURAL STONES,  
AGGLOMERATES, TERRACOTTA, TUFF**



Prevents surfaces from flaking. **WET ECO** withstands traffic: it can be used on outdoor areas subject to vehicle traffic, near barbecues and kitchens.



### COVERAGE

With one litre:

Unpolished stones and agglomerates 10/20 m<sup>2</sup>

Terracotta 7/20 m<sup>2</sup>

"Coverage shown is for guidance purposes only and refers to single coats"

### Packaging

1 litre: boxes of 12.

5 litres: boxes of 4.

### WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.

### TEMPERATURES

Storage temperature: from 5° to 30° C.  
This product must be applied to surfaces with temperature between 10°C and 30°C.

### WHAT IT'S FOR

- Stain protector and anti-dirt product with wet effect for unpolished natural stone surfaces, unpolished agglomerates and terracotta.
- Prevents the absorption of stains and facilitates dirt removal.
- It is particularly suited for exterior use and also effective for interiors.
- Prevents surfaces from flaking.

### ADVANTAGES

- Ecological treatment: water-based
- High resistance to intense traffic.
- Resistant to weathering.
- Does not peel nor yellow.
- Facilitates subsequent maintenance.
- Does not alter the frost resistance of terracotta (UNI EN ISO 10545-12).
- This product has extremely low VOC emissions: certified by GEV and EC1Plus-marked, it helps to obtain LEED credits.
- An A+ certified product in accordance with the French VOC regulation.
- Product conforming to:
  - French CMR components
  - AgBB
  - Belgium regulation

### HOW TO USE IT

**No dilution required:** ready to use.

**Application:** Shake before use.

Apply **WET ECO** evenly and continuously to a clean and dry surface using a flat paintbrush or fleece pad, wetting the grout lines as well. Apply a second coat of the product 2-3 hours later following the same method. Wait at least 12 hours before walking on the surface.

**Maintenance:** diluted solution of **CLEANER PRO**.

### Caution:

*For surfaces with low absorbency (slate, Botticino or Carrara marble) we recommend diluting the product with water (1 litre of product to 1 litre of water). Do not use on polished surfaces. Do not apply the product externally if rain is forecast.*

*The product cannot be applied to supports with problems connected with rising damp.*

*If the product has been applied incorrectly or if thorough cleaning is required, remove **WET ECO** using **NOPAINT STAR**.*